



## Yealink W60P/W60B Cordless Set Specifications

### Phone Features

- > Up to 8 simultaneous calls
- > Up to 8 handsets
- > Up to 8 VoIP accounts
- > Up to 2 simultaneous calls per handset
- > Up to 5 repeaters per base station
- > Handset selection for receiving call
- > Handset and number selection
- > Paging, intercom, auto answer, dial plan
- > Call hold, transfer, 3-way conference
- > Switching between calls
- > Call waiting, mute, silence, DND
- > Caller ID with name, number
- > Anonymous call
- > Anonymous call rejection
- > Call forward (always/busy/no answer)
- > Speed dial, voicemail, redial
- > Message Waiting Indication (MWI)
- > Local phonebook, up to 500 entries (in the base)
- > Remote phonebook/LDAP
- > Phonebook search/import/export
- > Call history (all/misplaced/received)
- > Direct IP call without SIP proxy
- > Reset to factory, reboot
- > Keypad lock, emergency call, music on hold
- > BroadSoft directory, BroadSoft call log
- > BroadWorks feature key synchronization
- > Shared Call Appearance (SCA)

### Personalization

- > 9 ringer melodies
- > Screen saver
- > Multilingual user interface

### Management

- > Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- > Auto-provision with PnP
- > Handset upgrade: OTA (Over-The-Air)/USB port
- > Configuration: browser/phone/auto-provision
- > Trace package and system log export

### Audio Features

- > Full-duplex speakerphone
- > Hearing Aid Compatibility (HAC)
- > Receiver volume control: 5 steps
- > Ringer volume control: 5 steps+off
- > Multiple advisory tones
- > Acoustic warning for low battery status
- > DTMF
- > Wideband codec: Opus, AMR-WB (optional), G.722
- > Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
- > VAD, CNG, AEC, AGC, PLC, AJB
- > Support VQ-RTCPXR (RFC6035)

### Network Features

- > SIP v1 (RFC2543), v2 (RFC3261)
- > SNTP/NTP
- > VLAN (802.1Q and 802.1P)
- > 802.1x, LLDP, PPPoE
- > STUN Client (NAT Traversal)
- > UDP/TCP/TLS
- > IP assignment: static/DHCP
- > Support outbound proxy server backup

### Security

- > Open VPN
- > Transport Layer Security (TLS)
- > HTTPS (server/client), SRTP (RFC3711)
- > Digest authentication using MD5
- > Secure configuration file via AES encryption
- > Support SHA256/SHA512/SHA384
- > Three-level configuration mode: Admin/Var/User

### DECT

- > Frequency bands: 1880 – 1900 MHz (Europe); 1920 – 1930 MHz (US)
- > DECT Standards: CAT-iq2.0

### Interface

- > 1 x RJ45 10/100M Ethernet port
- > Power over Ethernet (IEEE 802.3af), Class 1
- > Headset jack (3.5 mm)

### Physical Features

- > Indoor range: 20m~50m (ideal distance is 50m)
- > Outdoor range: 300m (in ideal conditions)
- > Standby time: 400 hours (in ideal conditions)
- > Talk Time: 30 hours
- > 2.4" 240x320 pixels color display
- > Desktop or wall mountable
- > LCD backlit, key backlit
- > Energy-saving ECO mode/ECO Mode+
- > 12 key numerical keypad, 5 navigation keys, 2 softkeys, 6 function keys, 6 shortcut keys
- > Three LED indicators on W60B: - 1 x Registration LED - 1 x Network Status LED - 1 x Power Indicator LED
- > External Yealink AC adapter: AC 100-240V Input and DC 5V/600mA Output
- > Phone size: 175mm x 53mm x 20.3mm
- > Base station size: 130mm x 100mm x 25.1mm
- > Operating humidity: 10~95%
- > Operating temperature: -10~+50°C (+14~122°F)

### Package Features

- > Package content:
  - W56H Handset
  - W60B Base Station
  - Base Stand
  - USB Charger Cradle
  - Two Power Adapters
  - Ethernet Cable
  - Belt Clip
  - Rechargeable Battery
  - Quick Start Guide
  - Handset Protective Case (optional)
- > Qty/CNT: 10 PCS
- > Giftbox size: 205mm\*196mm\*95mm
- > Carton meas: 495mm\*406mm\*223mm
- > N.W: 7.5 kg
- > G.W: 8.3 kg